

Instruction for the use of the LED power supply

The LED power supply LED-NT06-12VF is exclusively designed for the LED lamps used in indoors. It is a switch mode power supply with 12 V DC constant output voltage.

An electronic protection circuit switches off the power supply in case of short circuit or overload in the secondary circuit, overheat as well as open circuit. After the removing of the faults, the LED power supply is resetting automatically for operation again.

Important information for the installation

The unit conforms to the directive **2004/108/EC** for the electromagnetic compatibility and the low voltage directive **2006/95/EC**.

- The LED power supply can only be used with LED lamps
- The LED power supply is for indoor use only. Protect the LED power supply against excessive heat (permissible operating temperature range -20 to +45 °C).
- The loads indicated on the power supply must neither exceed nor below the following values

LED-NT06-12VF: 0-6 W

- Connect the LED lamps to the LED power supply with correct polarity according to the schematic drawing.
- The maximum length of the output cable to the LED lamps should not exceed 2 m in order to meet the EMC standard.
- If the LED power supply is used for purposes other than originally intended or it is connected in the wrong way, no liability can be taken over for possible damages.

Specifications:

Input voltage:	200-240 V +/-10%, 50 Hz
Input current:	< 0.10 A
Output voltage:	12 V DC +/-0.5 V
Rated power:	6 W
Protection type:	IP20
Ambient temperature t_a :	max. 45 °C
Case temperature t_c :	max. 75 °C
Primary cable:	H03VVH2-F 2.x0.75 mm ²
Secondary cable:	H03VVH2-F 2x0.75 mm ²

